

Barite 4.2

Description

Barite 4.2 is created by grinding barium sulfate mineral to meet API specification 13A for drilling fluid applications. It is chemically inert and insoluble in water. It does contain impurities such as quartz and calcite.

Barite 4.2 contains very low levels of heavy metals to meet the most stringent environmental regulations.

Applications

Barite 4.2 has the capability to weight up fluids up to 22 ppg with acceptable rheological properties. Additionally, it can be used to make plugs and pills for well-control operations, hole cleaning and/or wellbore displacement.

Features and Benefits

- Cost effective
- Industry standard weighting agent
- Chemically inert

Typical Properties

Appearance	Powder
Specific Gravity	4.20 Min
Residual greater than 75 microns	3% Max
Residual less than 6 microns	30% Max

Recommended Treatment

The amount of Barite 4.2 required to weight up a fluid is shown in the equation below:

Required Barite 4.2, ppb

$$= 1470 * \frac{\text{Final Density, ppg} - \text{Initial Density, ppg}}{35.0 - \text{Final Density, ppg}}$$

Barite 4.2 should not be used in concentrated potassium or cesium formate brines, as it will produce barium ions, which are hazardous.

Safety and Handling

Prior to using this product, refer to the safety data sheet for information on use of personal protective equipment, safe handling, storage, transport, and disposal.

Packaging

Barite 4.2 is available in 50 lb (22.7 kg), 55 lb (25 kg), 100 lb (45.4 kg), 1 MT sacks and in bulk.

No representations or warranties, either express or implied, of merchantability, fitness for a specific purpose, and/or that the products to which the information referred to in this document may be used without infringing the intellectual property rights of others, or of any other nature, are made with respect to information provided in this document, or the products referred to herein. In no case shall the information be considered a part of our terms and conditions of sale of QMax products or services. Use of the information provided in this report is at the user's risk.

“Excellence, Innovation, Integrity, Teamwork and Safety”

www.qmax.com – 11700 Katy Fwy, Ste 200, Houston, TX 77079 – Tel.: 832 672 4476