

Carbonato de Calcio M40-100

Description

Carbonato de calcio M40-100 is a compound with formula CaCO_3 that occurs naturally as limestone, marble or chalk. It is an additive used as bridging – sealing agent to minimize invasion of filtrate and whole fluid to the formation. It is 98 – 99.5% acid soluble.

Applications

Carbonato de calcio M40-100 can be used alone or in combination with other LCM material. Acting as a bridge in the fractures and pores of the formation being drilled, it will minimize losses to the formation while circulating and in static conditions. It can be used in drilling, completion and workover fluids.

Features and Benefits

- Used as bridging agent in sandstones and permeable formations
- Agent for wellbore strengthening when drilling depleted zones
- Combined with other sealing agents minimizes and/or controls seepage and severe losses
- Minimizes formation damage

Typical Properties

Appearance	Solid
Color	White
Specific Gravity	2.7
Molecular Weight	100.87
D50 (microns)	Approx. 300

Recommended Treatment

Carbonato de calcio M40-100 is generally used in fluid loss control situation requiring a larger particle size than Carbonato de Calcio 200 or finer. Typical concentration for bridging purposes is 20 – 50 lb/bbl (85.5 – 142.5 kg/m³).

Carbonato de calcio 40-100 is not usually used as weighting agent, in case it is used for that purpose, the following is the formula for obtaining the amount of CaCO_3 required in lb/bbl:

$$= 945 * \frac{\text{Final density, lb/gal} - \text{Initial density, lb/gal}}{22.5 - \text{Final density, lb/gal}}$$

Safety and Handling

Prior to using this product, refer to the safety data sheet for information on use of personal protective equipment, safe handling, storage, transport, and disposal.

Packaging

Carbonato de calcio M40-100 is available in 110 lb (50 kg) bags and in bulk.

No representations or warranties, either express or implied, of merchantability, fitness for a specific purpose, and/or that the products to which the information referred to in this document may be used without infringing the intellectual property rights of others, or of any other nature, are made with respect to information provided in this document, or the products referred to herein. In no case shall the information be considered a part of our terms and conditions of sale of QMax products or services. Use of the information provided in this report is at the user's risk.

“Excellence, Innovation, Integrity, Teamwork and Safety”

www.qmax.com – 11700 Katy Fwy, Ste 200, Houston, TX 77079 – Tel.: +1 (832) 672 4476